KELINE

Keystone Jack, Category 6A, RJ45/s

P/N: KEJ-CEA-S-10G

10	Cat. 6A	500
Gigabit	system	MHz



Features

- tool-free, fast and easy installation
- enables transmission of all high-speed protocols including 10GBASE-T
- guarantees a bandwidth of 500 MHz
- perfectly shielded against Alien Crosstalk and electromagnetic interference
- suitable for a wide range of outlets, duct and channel systems

Application

- primary (Campus), secondary (Riser), tertiary (Horizontal)
- IEEE 802.3: 10BASE-T; 100BASE-T; 1000BASE-T; 10GBASE-T
- IEEE 802.5: 16 MB; ISDN; FDDI; ATM
- high bandwidth digital applications with low BER
- multimedia transmissions like digital and analog video and voice

Mechanical properties

Suitable for installing on cables		with solid wires from 0,51 to 0,64 mm (from AWG 24 to AWG 22)
Required installation depth		sockets with angled faceplates 15 - 40 mm
		sockets with straight faceplates 40 mm
Insertion / extraction cycles		min. 750
Temperature range	operation	-40°C to +70°C
	installation	-10°C to +60°C
IDC reterminations		min. 20
Contact pin material		phosphor-bronze alloy coated with 6 μ gold

Electrical properties at 20°C

Current rating	1,25 A max
Contact resistance of spring	100 mΩ max
Contact resistance of IDC	2,5 mΩ max
Dielectric strengtht	750 Vac / 1 minute contact/contact
Dielectric strenght	1000 Vac / 1 minute contact/panel